Spółdzielnia - Zakład Pracy Chronionej
21-300 Radzyń Podlaski ul. Gen. Fr. Kleeberga 10

Air pressure rise sensor

Voltage rating: 12 V - 24 V
Power rating: 48 W
Max. safe pressure 2943 kPa
Applications: trucks, buses.



Part number	Required pressure	Kind of thread	Terminal variety
501.13.20	$14{,}7\ ^{+4{,}9}_{-9{,}8}$ kPa ($0{,}15\ ^{+0{,}05}_{-0{,}1}$ kG/cm^2)	Metric thread 12 x 1,5	Flat
501.14.20	$49^{\pm 9{,}8}$ kPa ($0{,}5^{\pm 0{,}1}$ kG/cm^2)		Flat
501.17.20	$196^{\pm 49}$ kPa ($2^{\pm 0{,}5}$ kG/cm^2)		Round

Voltage rating: 12 V - 24 V
Power rating: 48 W
Max safe pressure 2943 kPa
Applications: trucks, buses.



Part number	Required pressure	Kind of thread	Terminal variety
501.15.20	$441^{\pm 49}$ kPa ($4{,}5\ ^{\pm 0{,}5}$ kG/cm^2)	Metric thread 12 x 1,5	Flat
501.16.20	$539\ ^{\pm 49}$ kPa ($5{,}5\ ^{\pm 0{,}5}$ kG/cm^2)		Flat

Voltage rating: 12 V - 24 V
Power rating: 48 W
Max. safe pressure 2943 kPa
Applications: trucks.



Part number	Required pressure	Kind of thread	Terminal variety
501.18.20	$196\ ^{\pm 49}$ kPa ($2\ ^{\pm 0{,}5}$ kG/cm^2)	Taper thread 10 x 1	Flat

NIP:538-000-27-51
Home Office (083) 352 84 10
Trade Department (083) 352 84 42 fax 352 86 19

www.simena.com.pl
poczta@simena.com.pl
sprzedaz@simena.com.pl